



Facade-channel drainage system consisting of:

- **Channel Body** made of galvanized or stainless steel 1.4301, standard length 500/1000/2000mm
 - according to Austrian standard B3691:2012
 - Depending on the application - both-side perforated or closed channel, closed bottom
 - Different construction heights: Fixed heights: 55/90; variable heights: 55-90
 - Walkable and wheel chair accessible
- **Channel grates** walkable and wheel chair accessible, depending on the application made of galvanized or stainless steel 1.4301, with optional screw connection e.g.: mesh-grate MW30/10, perforated-grate Ø 6mm, Longitudinal- and cross-bar-grate, bar-distance 10 mm
- **Accessories:**
 - Outlet units made of galvanized or stainless steel 1.4301, in different heights, DN 100 bottom-outlet, closed
 - Cross-, corner- and T-pieces made of galvanized or stainless steel 1.4301, in variable heights
 - Front caps made of galvanized or stainless steel 1.4301
 - Screw-connection material made of stainless steel 1.4301 for all grates
 - Optional: odour trap (plastic)
 - Top section made of galvanized or stainless steel 1.4301: width 230/230 or 400/400, variable height
 - grates for top section made of galv. or stainl. steel 1.4301: mesh-grate MW30/10, perforated-grate Ø 6mm
 - Branch canals made of galv. or stainl. steel 1.4301: Length 1000/2000mm, width 90mm, height 30mm

Specification text:

1. Facade-drainage-channels, RB 250mm made of galvanized or stainless steel 1.4301 according to Austrian standard B3691:2012, both-side perforated or closed, walkable and wheel chair accessible.

Fixed heights:	55mm	90mm	
Variable heights:	55-90mm		
Length:	500mm	1000mm	2000mm
2. gratings made of galvanized or stainless steel 1.4301, with optional screw-connection, walkable and wheel chair accessible

Mesh-grating:	length: 1000/500mm, MW30/10 - galvanized or stainless steel		
Perforated-grate:	length: 1000/500mm, Ø 6mm - galvanized or stainless steel		
Longitudinal-bar-grate:	length: 1000/500mm, bar-distance 10 mm - galvanized or stainless steel		
Cross-bar-grate:	length: 1000/500mm, bar-distance 10 mm - galvanized or stainless steel		
3. Outlet units made of galvanized or stainless steel 1.4301, standard-length 1000mm

Different heights:	fixed heights: 55/90mm closed	variable heights: 55-90
Bottom-outlet:	DN 100	
Optional:	odour trap made of plastic	
4. Front caps made of galvanized or stainless steel
5. Cross-, corner- and T-pieces made of galvanized or stainless steel with variable heights
6. odour trap made of plastic for bottom-outlet DN100
7. Screw-connection material made of stainless steel for all grates
8. Top section made of galv. or stainl. steel: different width 230/230 or 400/400 and variable heights (55-90mm, 90-150mm)
9. Grates for top section made of galv. or stainl. steel: mesh-grate MW30/10, perforated-grate Ø 6mm
10. Branch canal made of galv. or stainl. steel: length 1000/2000mm, width 90mm, height 30mm