BG-TE terrace slot-channel system consisting of:

- **Channel body** made of stainless steel 1.4301 (AISI 304), standard length 1000 mm
- Fix height: 100 mm
- Variable height: 80-130 mm
- Width 100 mm
- Slot width: 18mm
- Depending on application both sides perforation or non-perforated
- Walkable and wheel chair accessible

- **Channel grates:** slot inlay with square holes 8/8 mm, walkable and wheelchair accessible, made of stainless steel, width 18 mm, length 500/1000 mm
  Construction time barrier made from wood width 18 mm, length 1000mm, recommended for construction phase

- **Accessories:**
  - Stainless steel maintenance unit, opening size 500/100, height 80-130 mm, vertical outlet DN 75 / horizontal outlet DN 50
  - Inside and outside corner pieces made of stainless steel, length 200/200, height 80-130 mm
  - End caps made of stainless steel for left and right side, width 100 mm, height 80-130 mm
  - stainless steel branch canal: length 1000/2000mm, width 90 mm, height 30 mm

Specification text:

1. BG-TE terrace slot-channels, slot width 18 made of stainless steel 1.4301 (AISI 304), perforated or non-perforated walkable and wheel chair accessible

Fix height:	100 mm
Variable height:	80 -130 mm
Length:	1000 mm

2. Slot inlay with square holes 8/8 mm, walkable and wheelchair accessible, made of stainless steel, width 18 mm, length 500/1000 mm
   Construction time barrier made from wood width 18 mm, length 1000mm, (to protect from damage and soiling during construction phase)

3. Stainless steel maintenance unit, opening size 500/100, height 80-130 mm, vertical outlet DN 75 / horizontal outlet DN 50

4. Inside and outside corner pieces made of stainless steel, length 200/200, height 80-130 mm

5. End caps made of stainless steel for left and right side, width 100 mm, height 80-130 mm

6. Gully top made of stainless steel: width 250/250 or 400/400 and fixed (50mm) and variable heights (70-100mm, 100-160mm)

7. Stainless steel branch canal: length 1000/2000mm, width 90 mm, height 30 mm