

**Declaration of performance (EN) according to EU
Construction Products Regulation No. 305/2011**




GRASPOINTNER
Sustainable innovation.

No. DoP-175-BG

V6



BG-FILCOTEN®

1. Unique identification code of the product-type:	Plastic grates and covers for FILCOTEN HPC (High Performance Concrete) channels for vehicular and pedestrian areas according to standard EN 1433													
2. Type, batch or serial number required pursuant to Article 11(4):	BG-FILCOTEN® tec, pro Kl. C 250													
channel-type:	<u>articlenumbers according to currently valid brochure/price list:</u>													
tec/pro NW 100:	17010402, 17010404													
3. Intended use as foreseen by the manufacturer:	grates and covers integrated in linear drainage systems													
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	BG-Graspointner GmbH Gessenschwandt 39, A-4882 Oberwang Telefon: +43 (0) 6233 / 8900-0 / Fax: +43 (0) 6233 / 8900-303 E-Mail: office@bg-graspointner.com													
5. Name and contact address of the authorised representative specified in Article 12(2):	not applicable													
6. System for assessment and verification of constancy of performance	system 3													
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:	The notified body [NB-Nr. 1794] <u>KIWA GmbH, Augsburg als Prüfstelle der PÜZ Bau GmbH</u> <u>Mühlmahdweg 25 a, 86167 Augsburg</u> based on type testings for drainage channels on the basis of solid BG-Graspointner samples, has determined compliance with the requirements specified by the standard.													
8. Declared performance:	<table border="1"> <thead> <tr> <th data-bbox="204 1328 635 1350">essential characteristics</th> <th data-bbox="668 1328 1066 1350">performance</th> <th data-bbox="1099 1328 1473 1350">harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td data-bbox="204 1384 635 1429">Water tightness - connection of elements</td> <td data-bbox="668 1395 1066 1417">NPD</td> <td data-bbox="1099 1473 1329 1496" rowspan="4">EN 1433:2002/A1:2005</td> </tr> <tr> <td data-bbox="204 1435 635 1480">Load capacity - maximum load</td> <td data-bbox="668 1447 1066 1469">Kl. C 250</td> </tr> <tr> <td data-bbox="204 1487 635 1532">Deformation under load - permanent deformation</td> <td data-bbox="668 1498 1066 1520">Kl. C 250</td> </tr> <tr> <td data-bbox="204 1547 635 1570">durability</td> <td data-bbox="668 1559 1066 1581">NPD</td> </tr> </tbody> </table>		essential characteristics	performance	harmonised technical specification	Water tightness - connection of elements	NPD	EN 1433:2002/A1:2005	Load capacity - maximum load	Kl. C 250	Deformation under load - permanent deformation	Kl. C 250	durability	NPD
essential characteristics	performance	harmonised technical specification												
Water tightness - connection of elements	NPD	EN 1433:2002/A1:2005												
Load capacity - maximum load	Kl. C 250													
Deformation under load - permanent deformation	Kl. C 250													
durability	NPD													
9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:	Signed for and on behalf of the manufacturer by: Oberwang, 30.08.2023 (place and date of issue)	 <p>GRASPOINTNER sustainable innovation.</p> <p>BG-Graspointner GmbH A-4882 Oberwang, Gessenschwandt 39 Telefon 06233/8900-0, www.bg-graspointner.com Günther Baumgartner, COO (name and function)</p>												