

1. **Facade channel BG-FLEX FA RB 130** made of galvanized steel or stainless steel 1.4301, walkable and wheel chair accessible, according to Austrian standard B3691:2019, length 500, 1000 mm, 2000 mm, both-side perforated or non-perforated channel, Delivery and installation according to the manufacturer's installation instructions.

Channel type:	LxWxH: [mm]	weight: [kg]
RB 130, H 80:	500x130x80	1,4
RB 130, H 80:	1000x130x80	2,5
RB 130, H 80:	2000x130x80	5,0
RB 130, H 180:	1000x130x80	4,1
RB 130, H 180:	2000x130x80	8,1

-
2. **Covers/Grates** made of galvanised steel or stainless steel 1.4301, optional screw connection
-

BG-FLEX FA mesh grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, MVV 30/10, length 1000 mm

BG-FLEX FA mesh grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, MVV 30/10, length 500 mm

BG-FLEX FA perforated grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, Ø 6mm, length 1000 mm

BG-FLEX FA perforated grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, Ø 6mm, length 500 mm

BG-FLEX FA slotted grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, SVV 9/85, length 1000 mm

BG-FLEX FA slotted grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, SVV 9/85, length 500 mm

BG-FLEX FA longitudinal bar grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, bar distance 10mm, length 1000 mm

BG-FLEX FA longitudinal bar grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, bar distance 10mm, length 500 mm

BG-FLEX FA cross bar grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, bar distance 10mm, length 1000 mm

BG-FLEX FA cross bar grating RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, bar distance 10mm, length 500 mm

BG-FLEX FA design grating "rays" RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, length 1000 mm

BG-FLEX FA design grating "rays" RB 130, galvanized steel or stainless steel walkable and wheelchair accessible, length 500 mm

-
3. **Outlet unit** made of galvanized steel or stainless steel I.430I
Bottom outlet DN 75
length 1000 mm / width 130 mm / height 80 or 180 mm
Delivery and installation according to the manufacturer's installation instructions.
height 80: 2,6 kg
height 180: 4,3 kg
-
4. **front cap** closed, made of galvanized steel or stainless steel I.430I
H 80: 0,1 kg
H 180: 0,2 kg
-
5. **corner element** made of galvanized steel or stainless steel I.430I
H 80: 2,1 kg
-
6. **KIT-bolting material** for mesh grating and longitudinal bar grating, made of stainless steel I.430I, consisting of clamp, screw and nut (requirement: 2 pcs./m)
-
7. **Gully top** made of galvanized steel or stainless steel I.430I, with fixed or variable height:
- size 250/250 mm
H 50: 1,9 kg
H 70-100: 2,6 kg
H 100-160: 2,9 kg
- size 400/400 mm
H 50: 2,4 kg
H 70-100: 3,3 kg
H 100-160: 4,1 kg
-
8. **Grating for gully top** made of galvanized steel or stainless steel I.430I, mesh grating MW 30/10, H 20 mm
size 250/250 mm 1,3 kg
size 400/400 mm 2,5 kg
-
9. **Branch canal** made of galvanized steel or stainless steel I.430I, L 1000/2000 mm, W 90 mm, H 30 mm
-
10. **Gravel stop** made of aluminium, L 2000 mm, B/H 50/30 mm or 80/50 mm
-