## Tender-text:

## **BG-FILCOTEN** one NW 150



Version: 04/2020

1. prefabricated **side-strip slabs LEFIX** with attachment concrete and a concrete quality of at least C30/37

XC3/XD3/XF4/XA1 (increased frost and de-icing salt resistance)

Complete surface of the slab with a gradient to the outside of at least 3 percent

Groove-like tread structure, transverse to the direction of travel, for generation of:

- a rumble or warning effect when passing over
- a controlled, even drainage of the roadway

Tapered end faces for inner and outer radii

Toothing with tongue and groove for a non-displacing composite effect

Integrated spacers to prevent chipping during transport, storage and installation

The side-strip slabs must be laid in accordance with the manufacturer's installation instructions.

Type: LxWxH: [mm] Weight: kg] Installation radius: [m] Colour of attachment:

1000/500: 1000x500x140/125 149 > 12 grey / red

2. prefabricated **side-strip slabs LEFIX** as described in pos. I, but,

with length 450 mm and laying radius 6 m

Type: LxWxH: [mm] Weight: [kg] Installation radius: [m] Colour of attachment:

450/500: 450x500x140/125 65 > 6 grey / red

3. prefabricated side-strip slabs LEFIX as described in pos. I, but,

with length 250 mm and laying radius 6 m

Type: LxWxH: [mm] Weight: [kg] Installation radius: [m] Colour of attachment:

250/500: 250x500x140/125 36 > 4 grey / red

4. prefabricated **side-strip slabs LEFIX** as described in pos. 1, but,

with **opening for reflector post**, length 1000 mm, colour grey

Type: LxWxH: [mm] Weight: [kg] Installation radius: [m] Colour of attachment:

1000/500 LPF: 1000x500x140/125 145 > 12 grey

5. prefabricated **side-strip slabs LEFIX** as described in pos. I, but,

with width 350 mm, length 1000 mm

Type: LxWxH: [mm] Weight: [kg] Installation radius: [m] Colour of attachment:

1000/350: 1000x350x140/130 107 > 16 grey / red

6. additional charge reflection area, I pc. groove profile per side-strip slab

Colour: red or white

7. lifting clamp, max. load 250 kg, weight 15 kg, opening width 55 - 535mm, for purchase or rental