

**Declaration of performance (EN) according to EU  
Construction Products Regulation No. 305/2011**





**GRASPOINTNER**  
Sustainable innovation.

No. DoP-115-BG

V5



**BG-FILCOTEN®**

1. Unique identification code of the product-type:	drainage channels out of concret - FILCOTEN® HPC (High Performance Concrete) - for vehicular and pedestrian areas according to standard EN 1433													
2. Type, batch or serial number required pursuant to Article 11(4):	<b>BG-FILCOTEN® one</b> Typ M - Kl. F 900													
<b>channel-type:</b>	<b>articlenumbers according to currently valid brochure/price list:</b>													
one NW 150: one NW 200:	15015.. 15020..													
3. Intended use as forseen by the manufacturer:	drainage channels for vehicular and pedestrian areas													
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	BG-Graspointner GmbH Gessenschwandt 39, A-4882 Oberwang Telefon: +43 (0) 6233 / 8900-0 / Fax: +43 (0) 6233 / 8900-303 E-Mail: office@bg-graspointner.com													
5. Name and contact address of the authorised representative specified in Article 12(2):	not applicable													
6. System for assessment and verification of constancy of performance	system 3													
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:	The notified body [NB-Nr. 1661] OÖ. Boden- und Baustoffprüfstelle GmbH Schirmerstraße 12, A-4060 Leonding based on type testings for drainage channels on the basis of solid BG-Graspointner samples, has determined compliance with the requirements specified by the standard.													
8. Declared performance:	<table border="1"> <thead> <tr> <th data-bbox="181 1335 639 1384">essential characteristics</th> <th data-bbox="639 1335 1070 1384">performance</th> <th data-bbox="1070 1335 1513 1384">harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td data-bbox="181 1384 639 1442">Water tightness - connection of elements</td> <td data-bbox="639 1384 1070 1442">fulfilled</td> <td data-bbox="1070 1384 1513 1599" rowspan="4">EN 1433:2002/A1:2005</td> </tr> <tr> <td data-bbox="181 1442 639 1496">Load capacity - maximum load</td> <td data-bbox="639 1442 1070 1496">Kl. F 900</td> </tr> <tr> <td data-bbox="181 1496 639 1554">Deformation under load - permanent deformation</td> <td data-bbox="639 1496 1070 1554">NPD</td> </tr> <tr> <td data-bbox="181 1554 639 1599">durability</td> <td data-bbox="639 1554 1070 1599">W +R</td> </tr> </tbody> </table>		essential characteristics	performance	harmonised technical specification	Water tightness - connection of elements	fulfilled	EN 1433:2002/A1:2005	Load capacity - maximum load	Kl. F 900	Deformation under load - permanent deformation	NPD	durability	W +R
essential characteristics	performance	harmonised technical specification												
Water tightness - connection of elements	fulfilled	EN 1433:2002/A1:2005												
Load capacity - maximum load	Kl. F 900													
Deformation under load - permanent deformation	NPD													
durability	W +R													
9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:	Signed for and on behalf of the manufacturer by:  Oberwang, 30.08.2023 (place and date of issue)	 <b>GRASPOINTNER</b> Sustainable innovation.   BG-Graspointner GmbH A-4882 Oberwang, Gessenschwandt 39 Telefon 06233/8900-0, www.bg-graspointner.com Günther Baumgartner, COO (name and function)												