



1. **Heavy-duty drainage-channel** BG-CLASSIC BGZ-S NW 300 made of concrete, with integrated Z-shaped cast iron edge, load-class A15 – F900 kN, according to EN1433 – CE-certified, channel joint with safety seam, sealable, length 1000 (2500) mm, without slope, Fire-behaviour class: A1 according to EN13501 - non-combustible 100% recyclable with U-A marking, Delivery and installation according to the manufacturer's installation instructions.

NW/No.:	LxWxH: [mm]	weight: [kg]
300 No. 0:	1000x399x395	169
300 CH 700:	2500x394x700	671
300 CH 700:	1000x394x700	269

2. **Heavy-duty drainage-channel** as described in position 1, but with **bottom outlet** DN 200 (Dm 226 mm),

NW/No.:	LxWxH: [mm]	weight: [kg]
300 No. 0:	1000x399x395	162
300 CH 700:	1000x394x700	258

3. **Covers/Grates** made of galvanised steel or ductile iron
with integrated longitudinal movement protection and quick-locking system (SV),
load class C250kN – E600kN, according to EN1433 - CE-certified
-

BG-CLASSIC SV **mesh grating** NW 300, steel galvanised steel
cl. C250, MW 30/10, length 1000 mm,
with integrated longitudinal movement protection and quick-locking system (SV), according to EN1433 – CE- certified

BG-CLASSIC SV **mesh grating** NW 300, galvanised steel
cl. C250, MW 30/10, length 500 mm,
with integrated longitudinal movement protection and quick-locking system (SV), according to EN1433 – CE- certified

BG-CLASSIC SV **ductile iron slotted grating** NW 300, cast iron EN-GJS
cl. D400, SW 18/150, length 500 mm
with integrated longitudinal movement protection and quick-locking system (SV), according to EN1433 – CE- certified

BG-CLASSIC SV **main bar grating** NW 300, cast iron EN-GJS
cl. E600, MW 25/14, length 500 mm
with integrated longitudinal movement protection and quick-locking system (SV), according to EN1433 – CE- certified

4. **Covers/Grates** made of cast iron **inclusive bolting material 4-times**,
with integrated longitudinal movement protection,
load class E600kN – F900kN, according to EN1433 – CE - certified
-

BG-CLASSIC **main bar grating** NW 300, cast iron EN-GJS
cl. E600, MW 25/14, length 500 mm
with integrated longitudinal movement protection, inclusive bolting material 4-times, according to EN1433 – CE- certified

BG-CLASSIC **ductile iron slotted grating** NW 300, cast iron EN-GJS
cl. F900, SW 16/148, length 500 mm
with integrated longitudinal movement protection, inclusive bolting material 4- times, according to EN1433 – CE- certified

Optional accessories cover:

SET- bolting material for mesh grating
steel, galvanised – consisting of 1 Stk. screw and 1 Stk. Mutter

SET- bolting material for cast grating
steel, black galvanised – consisting of 1 Stk. screw and 1 Stk. Mutter



5. **sump unit** BG-CLASSIC BGZ-S NW 300 concrete, 2 parts
with integrated cast iron frame
outlet: RDS DN 200
length 550 mm / width 565 mm / height 990 mm
Delivery and installation according to the manufacturer's installation instructions.
weight: 214 kg

6. **silt bucket** to sump unit, plastic
weight: 3,2 kg

7. **drain trap** made of PVC duct bends DN 200/87°, plastic
weight: 7,4 kg

8. **foreheda-sealing** for bottom outlet DN 200, Elastomer
weight: 0,6 kg

9. **front cap** closed off galvanized steel
weight: 1,3 kg

10. **end cap with outlet** DN 200 off galvanized steel
weight: 1,2 kg
