

HEELPROOF Ductile iron grating "VILLE"



Product Features:

- Certified to EN 1433
- Load Class E 600 kN (134,800 lbs per foot)
- Uses four point bolting system
- Suitable to use with NW300 channels
- Manufactured from ductile iron
- Heelproof
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings BG-FILCOTEN® pro NW 300 (12") with 4-point bolting.

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross-section cm2/m
							Lbs	Kg		
○	17030180	HEELPROOF grating "VILLE"	ductile iron	19.70"/13.70"/0.98" 500/348/25	E 600 kN	0.31" wide slots (SW 8mm)	43.87	19.9	82.2	530
○	32110	Bolts/nuts kit for class E ductile iron bar grating (4 pcs. required for 500mm grating)						0.2		

Specification: BG-FILCOTEN pro-G NW300, extra heavy duty, (Load Class E 600 kN), ductile iron, reinforced grate is 13.70" (348mm) wide, 19.70" (500mm) long, 0.98" (25mm) high, weighing 43.87 lbs (19.9 kg). The grate has 0.31" (8mm) wide slots and is Class E load rated - for commercial solid tire traffic patterns, and impacts from steel struts or metal wheels (forklifts). The grate is secured to the body with four point bolting system. Ductile iron manufactured and tested according to EN1433 - CE certified.

E600kN SW8mm: GJS 17030180,
 4-times bolted

