

HEELPROOF Ductile iron grating "VIA"



Product Features:

- Certified to EN 1433
- Load Class D 400 kN (89,920 lbs per foot)
- Uses four point bolting system
- Suitable to use with NW300 channels
- Manufactured from ductile iron
- Heelproof
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings BG-FILCOTEN® pro NW 300 (12") with 4-point bolting.

| | Item no. | Gratings | Material | Dimension | Load class as per EN-standard | Slot-/Mesh width | Weight | | Inlet cross-section sq.inches/m | Inlet cross-section cm2/m | |
|---|----------|---|--------------|-----------------------------------|-------------------------------|-------------------------------|--------|------|---------------------------------|---------------------------|--|
| | | | | | | | Lbs | Kg | | | |
| ○ | 17030184 | HEELPROOF grating "VIA" | ductile iron | 19.70"/13.62"/0.98" 500/346/25 | D 400 kN | SW 1.41"x 0.23" (SW29x6mm) | 38.58 | 17.5 | 153.4 | 990 | |
| ○ | 32110 | Bolts/nuts kit for class D ductile iron bar grating (4 pcs. required for 500mm grating) | | | | | | | 0.2 | | |

Specification: BG-FILCOTEN pro NW300, extra heavy duty, Load Class D 400 kN, ductile iron, reinforced grate is 13.62" (346mm) wide, 19.70" (500mm) long, 0.98" (25mm) high, weighing 38.58lbs (17.5 kg). The grate has 1.41"x0.23" (29x6mm) mesh width and is ADA compliant, Heelproof and Class D load rated - for pneumatic forklift traffic, roads and highways. The grate is secured to the body with four point bolting system. Ductile iron manufactured and tested according to EN1433 - CE certified.

D400kN SW29x6mm: GJS 17030184

