

**Ductile iron slotted grating**



**Product Features:**

- Certified to EN 1433 Load Class D 400 kN 89,920 lbs per foot.
- Uses fiX self-locking system and additional four point bolting.
- Suitable to use with NW300 channels.
- Manufactured from ductile iron

**Installation:**

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings BG-FILCOTEN® pro V NW 300 (12") with fiX self-locking system and additional 4-point bolting.

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross-section cm2/m
							Lbs	Kg		
○	17030108	Ductile iron slotted grating	ductile iron	19.70"/13.66"/0.98" 500/347/25	D 400 kN	0.63" wide x 11.81" slots (SW 16x300mm)	38.36	17.4	207.7	1340

**Specification:** BG-FILCOTEN pro-V NW300, extra heavy duty, (Load Class D 400 kN), ductile iron, reinforced grate is 13.62" (346mm) wide, 19.70" (500mm) long, 0.98" (25mm) high, weighing 49.16 lbs (22.3 kg). The grate has 0.63" (16mm) wide, 5.51" (140mm) long slots and is Class D load rated - for pneumatic forklift traffic, roads and highways. The grate is secured to the body with fiX self-locking system and additional four point bolting. Ductile iron manufactured and tested according to EN1433 - CE certified.

D400kN SW16/300: GJS 17030108

