

Slot Top 2S, HEELPROOF - Galvanized steel



Product Features:

- Certified to EN 1433
- Load Class C 250 kN or 56,200 lbs.
- Suitable to use with NW100 channels.
- Manufactured from galvanized steel.
- Heelproof
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and slot tops shall be installed in accordance with the manufacturer's installation instructions and recommendations.

SLOT TOP 2S asymmetric Heelproof BG-FILCOTEN light/tec/pro 100 (4")

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross-section cm2/m
							Lbs	Kg		
○	17111204	Slot top 2S SH=110m	galvanized steel	39.40"/4.84"/5.24" (1000/123/133)	C 250 kN	SW 2X0.24" (SW 2X6mm)	12.78	5.8	18.6	120
○	17111205	Slot top 2S, SH=110m	galvanized steel	19.70"/4.84"/5.24" (500/123/133)	C 250 kN	SW 2X0.24" (SW 2X6mm)	6.61	3.0	18.6	120

Specification: FILCOTEN Pave Slot Top 2S for NW100 trench drains, heavy duty, (Load Class C 250 kN), galvanized steel. The reinforced Slot Top is 4.84" (123mm) wide, 39.40" (1000mm) long, 5.24" (133mm) high, 11.9 lbs (5.4 kg) weight. FILCOTEN Pave has the double slot 2x0.24" (2x6mm) wide, and is HEELPROOF, ADA compliant and Class C - for commercial applications. The Slot Top 2Sand maintenance unit are suitable to use with nominal width 4" (100mm) trench drains. Galvanized steel manufactured and tested according to EN1433 - CE certified.

Slot top 2S:

C250kN SW 2x6mm / 2x0.24": V 17111204 and 17111205

