

HEELPROOF Pave Slot Top 2S (double slot) unit - Stainless steel



Product Features:

- Certified to EN 1433
- Load Class C 250 kN or 56,200 lbs.
- Suitable to use with NW100 channels.
- Manufactured from Stainless steel 1.4301.
- Heelproof
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and slot tops shall be installed in accordance with the manufacturer's installation instructions and recommendations.

SLOT TOP 2S asymmetric Heelproof BG-FILCOTEN light/tec/pro 100 (4")

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross-section cm2/m
							Lbs	Kg		
○	17111304	Slot top 2S SH=110mm	stainless steel	39.40"/4.84"/5.24" (1000/123/133)	C 250 kN	SW 2X0.24" (SW 2X6mm)	12.78	5.8	18.6	120
○	17111305	Slot top 2S, SH=110mm	stainless steel	19.70"/4.84"/5.24" (500/123/133)	C 250 kN	SW 2X0.24" (SW 2X6mm)	6.61	3.0	18.6	120

Specification: FILCOTEN Pave Slot Top 2S for NW100 trench drains, heavy duty, (Load Class C 250 kN), stainless steel. The reinforced Slot Top is 4.84" (123mm) wide, 39.40" (1000mm) long, 5.24" (133mm) high, 12.78 lbs (5.8 kg) weight. FILCOTEN Pave has 2 double slots of 0.24" (6mm) wide each, and is Heelproof and ADA compliant, Class C - for commercial applications. The Slot Top and maintenance unit are suitable to use with nominal width 4" (100mm) trench drains. Stainless steel manufactured and tested according to EN1433 - CE certified.

Slot top:

C250kN 2x6mm: E 17111304 (17111305)

